





### SPECIFICATIONS

| MODEL                         | WBK 15    | WPK 20                         | WBK 30                         |
|-------------------------------|-----------|--------------------------------|--------------------------------|
| <b>ENGINE</b>                 |           |                                |                                |
| Type                          | GK100     | GK200                          | GK200                          |
| Displacement (c.c.)           | 97        | 197                            | 197                            |
| Rated Output (HP)             | 1.5       | 3.0                            | 3.0                            |
| Fuel Starting                 | Petrol    | Petrol                         | Petrol                         |
| Running                       | Kerosene  | Kerosene                       | Kerosene                       |
| <b>PUMPSET</b>                |           |                                |                                |
| Size (mm)                     | 40x40     | 50x50                          | 80x80                          |
| Max.Head(Metres)              | 38        | 30                             | 28                             |
| Max.Discharge (Litre/Minute)  | 200       | 600                            | 1000                           |
| Rated Speed (RPM)             | 3800      | 3500                           | 3400                           |
| Total Weight of Pumpset (Kg.) | 14        | 26.5/29.5                      | 28/32                          |
| <b>FEATURES</b>               |           |                                |                                |
| Oil Alert                     | Yes       | Yes                            | Yes                            |
| Priming                       | Self      | Self                           | Self                           |
| Material of Pump              | Aluminium | Aluminium                      | Aluminium                      |
|                               | Alloy     | Alloy                          | Alloy                          |
| Multi Crop Lever              | Yes       | Yes                            | Yes                            |
| Carrying Arrangement          | Handle    | Handle/Tubular Frame(Optional) | Handle/Tubular Frame(Optional) |

...With Full Frame



WBK 15



WPK 20



WBK 30

#### HONDA QUALITY AT WORK

International Honda Technology delivers amazing performance when it comes to portable pumpsets. Low vibration, low noise, compact design & shortest self priming time are some of the key features that has made it favourite worldwide. Besides, many other design & material parameters enhance its overall performance.

- H** Cast Iron Impeller and mechanical seals allow you to have the minimum maintenance costs for Self Priming Pumpsets.
- H** Imported Zedellium Coated Fuel Tank avoids corrosion and keeps fuel clean.
- H** Oil bath Air Cleaner is suitable for dusty agricultural environment which ensures clean air to go inside the engine.
- H** Protector muffler made of special Imported Zinc Material, prevents from catching fire due to dry grass clippings.
- H** Yellow Passivated nuts & bolts ensure longer life and ease in maintenance due to dust-resistant property.
- H** Composite material fuel tube to prevent eventual fire hazards.

So, What are you waiting for? Contact your nearest Honda dealer.

**HONDA**  
POWER PRODUCTS

**AKASH**  
**POWER GENSETS**

Authorised Dealers For Honda  
Siel Power Products

Showroom & Sales Office : # 3, Opp : Veterinary College,  
Next to Cafe Coffee Day, Near CBI Office, Bellary Road,  
Ganganagar, Bangalore - 24. Tel : 080 4214 6675 / 4214 6692  
Mobile : 98452 04711 / 98458 40838 / 98455 41521  
Email : apg@akashpowergensets.com